#7

INSTALLATION MANUAL



MODEL FP-100 & FP-150

With New Quick Connect Components!

1999 - 2003
FORD POWERSTROKE
7.3L DIESEL ENGINE

PLEASE READ THESE INSTRUCTIONS THOROUGHLY
BEFORE BEGINNING INSTALLATION.

PureFlow AirDog

705 MAUSOLEUM ROAD
SHELBYVILLE, IN 46176

1-877-421-3187

www.pureflowairdog.com

PROTECTED BY

CANADIAN PATENT 2,108,391

US PATENTS 5,355,860; 5,746,184; 6,729,310

AUSTRALIAN PATENT 2005101054

NEW ZEALAND PATENT 532356

Additional Foreign Patents Pending in Europe, South America, Mexico, Japan, and China!

Approved for Sale and Use in California by CARB!

SMALL and COMPACT

7″ Long X 3.2″ Wide X 10″ Tall

OVERVIEW

Welcome to **PureFlow® AirDog®**

Fuel Air Separation, Filtration and Delivery System for the Diesel Engine

The AirDog® Fuel Air Separation system is a Premium lift pump and filtration system for the Ford PowerStroke diesel engine. A complete installation kit is included.

The AirDog® delivers clean fuel to the engine free of virtually all air/vapor and at a positive flow. Thus, allowing the engine "test cell" performance and efficiency, while in "real world" use.

The AirDog® FP-100 flows 100 GPH and is recommended for stock and slightly modified PowerStroke Diesels.

The AirDog® FP-150 is recommended for highly modified PowerStroke Diesels.

PureFlow products are manufactured with a personal touch,
unsurpassed attention to detail
and
the most stringent quality control!

TYPICAL INSTALLATION LAYOUT



Figure 1

The AirDog® draws fuel from the fuel tank at a constant flow, removing water, particulates, and air/vapor while maintaining a regulated pressurized fuel flow to the stock OE high pressure pump. The separated air/vapor is returned from the AirDog® to the fuel tank.

NOTE: The pictures used in this manual are for example only and may not be exactly the same as your truck.

QUICK CONNECT COMPONENT OVERVIEW

Provided in this kit is an OE style quick connection system. This system works to allow for a quick, clean, and professional install.

SAE J2044 Quick Connect System

The SAE J2044 quick connect system is the most commonly used system in the automotive industry. The images below show the formation of SAE J2044 connection. To connect the assemblies, simply insert the male end form into the mating female connector. Push firmly until you hear it “click” into place. To disconnect the fittings, press down and hold the blue tabs on the female connector while you firmly pull the assembly apart.

TABLE OF CONTENTS

Section 1……Table of Contents
Section 2……Installation and Safety Guidelines
Section 3……Parts List

INSTALLATION PROCEDURES

Section 4…… AirDog® & Mounting Brackets

FUEL LINES

Section 5 A……Fuel To High Pressure Pump
Section 5 B……Fuel Return to Tank
Section 5 C……Suction line For FP-100
Section 5 D……Suction Line For FP-150
(Includes Hi Flow Suction Tube)

ELECTRICAL HARNESS

Section 6……Electrical Harness
Section 7……Final Check List

MAINTENANCE

Section 8……Filter Service Recommendations
Section 9……Cleaning the Gerotor Assembly

Lifetime Limited Express Warranty

AirDog®
MODEL FP-100 & FP-150

The installation of your **AirDog®** can be made relatively easy by following the steps outlined in this manual, and:

1. Inventory the package components completely. Notify *PUREFLOW® AIRDOG* immediately of any parts missing or damaged.

2. Read the installation manual completely. Understand how the system operates and installation recommendations before beginning installation.

3. The installation recommendations contained herein are suggested installation guidelines only. Individual installations may vary.

4. If any installation procedure is uncertain, contact *PUREFLOW® AIRDOG* for technical assistance.

5. When installing the AirDog® fuel lines be sure to keep the ORIGINAL ENGINE RETURN LINE connected as it is from the factory!

SAFETY GUIDELINES!

CAUTION! Please be sure to chock the vehicle's tires to prevent rolling.

CAUTION! Please use proper supports when working beneath an elevated vehicle.

CAUTION! Most diesel pickups have two (2) 12volt batteries. Disconnect the battery cables to both batteries before proceeding with the AirDog® installation.

CAUTION! Vehicle frame rails should not be drilled into or welded upon.

CAUTION! Wear safety glasses when operating power tools such as drills and grinders or when using a punch or chisel.

CAUTION! Use common sense when routing fuel lines and electrical harnesses. Keep them away from hot exhaust components and/or moving parts. Properly secure lines to prevent chaffing.

Use Good Judgment and Common Sense When Installing the AirDog®!

PowerStroke Parts List

QTY	DESCRIPTION	Part Number	IMAGE
1	**Installation Manual**	ADI-F-100/150	
1	***AirDog®***	FP-100 *Or* FP-150	
1	**AirDog® Mounting Bracket**	001-3C-0004	
1	**Mounting Hardware Kit,**	901-61-0102-PM-F	
1	**Frame Bracket**	010-3C-0002PC 010-3C-0001PC	
1	**Wiring Harness**	5E-2-010	
1	**Return Fuel Filler Tube** (with 2 Clamps)	001-4A-1-0150	
1	**Bundle of Plastic Ties**	5H-2-1-06/12	
1	**High Flow Suction Tube** (For FP-150's Only)	WAP108	
1	**Grommet** (For FP-150's Only)	5J-1-1-04-0001	
1	**Spacer**	010-3C-0003-A-P	
1	**Suction Hose Assembly** (For FP-100 Only)	WAP110-8-6-90	
1	**Suction Hose Assembly** (For FP-150 Only)	WAP110-8-8-90	
1	**Return Hose Assembly**	WAP110-8-8-90	
1	**Pressure Hose Assembly**	WAP110-8-5	
1	**Customer Service Oring Replacement Kit**	901-05-0100	
2	**Push Lock Hose Splice**	001-4A-1-0026	
2	**1/2" Male SAE J2004 Quick Connect x 3/8" NPTF**	08J2044-3/8 NPTF	
1	**5/16" Fuel Pump Quick Connect**	4A-1-17-B-001	
1	**¼"Female NPT x ½" Push Lock**	4A-1-08-08-04-B	

ILLUSTRATION OF QUICK CONNECT COMPONENTS



DRAWING NOT TO SCALE

Installing the AirDog® & Mounting Brackets on the Truck's Frame!

Figure 2

Figure 3

Figure 4

4-1 Assemble the AirDog® mounting bracket to the frame bracket. Use the spacer block to adjust the AirDog® to clear lines and wiring harnesses on the frame. Also adjust the assembly up or down on the frame bracket as needed for clearance.

Figure 5

Mounted Outside the Frame

Figure 6

Figure 7

4-2 Install a 1/2" Male SAE J2004 Quick Connect x 3/8" (08J2044-3/8NPTF) into the "ENGINE" and "FUEL IN" ports in the AirDog®.

Figure 8

WARNING: The NPT fitting threads must be lubricated with oil or anti-seize compound before installation to prevent galling!

NOTE: The AirDog® can be mounted on either the outside of the frame or the inside, as space or personal choice dictates.

Outside the Frame

Figure 9

OR

Inside the Frame

Figure 10

Installing the AirDog® & Mounting Brackets on the Truck's Frame, cont'd!

NOTE: You may attach the AirDog® to the bracket either before or after attaching the assembly to the frame, whichever is easier for you. Mount the AirDog® so the "FUEL IN" port is directed toward the rear of the vehicle.

Figure 11

Figure 12

4-3. Loose assemble the AirDog® and brackets to the vehicle by clamping the frame between the mounting plate and back plate with bolts, lock washers, and nuts.

Figure 13

4-4. Position the AirDog® on the frame as necessary, for clearance. Properly torque the fasteners!

Fuel Supply Line from the AirDog® to the High Pressure Pump

Remove the original factory fuel supply line at the electric OE lift pump, located on the driver's side inside frame rail by squeezing the tabs on the end of the connector together. Push the quick connect fitting toward the OE lift pump while firmly depressing the tabs. With the tabs depressed, pull the fitting assembly from the inlet tube. Use care to hold the quick connect fitting squarely onto the inlet tube. It may be difficult to disconnect the fitting if it becomes cocked during removal.

With 5/16" Quick Connect Fitting



Figure 14 Figure 15

5A-1. Measure and cut the length of line on the "Pressure Hose Assembly" required to connect the 'Fuel to Engine' port on the AirDog® to the PowerStroke high pressure fuel pump.

5A-2. Assemble the ¼"Female NPT x ½" push lock to the 5/16" Quick Connect fitting.

Figure 16

Figure 17

5A-3. Insert the push lock quick connect assembly into the cut end of the hose. Oil can be used on the barb to ease the installation.

Figure 18

Figure 19

5A-4 Insert the female quick connect end (see figure 20) of the "pressure hose assembly" into the male quick connect fitting previously installed in the port marked "ENGINE". You will hear a "click" when it connects.

.

Figure 20

5A-4. Connect the end of the "Pressure Hose Assembly" 5/16" quick connect to the inlet of the factory high pressure pump (Fig 15)

Section 5B: Fuel Return Line from the AirDog® to the Tank!

Installing the fuel 'Return to Tank' assembly in Filler Tube



Figure 21

5B-1. Cut filler tube as illustrated, removing ½ inch. Loose assemble clamps on each end of filler tube.

Figure 22

Figure 23

Fuel Return Line from the AirDog® to the Tank Cont'd

5B-2. Insert "Return Fuel Filler Tube" assembly in filler tube. INSTALL THE FILLER TUBE WITH ARROWS POINTING TOWARD THE TANK!! SEE FIG 22 Properly tighten clamps.

5B-3. Insert the SAE J2044 female quick connect end(see Figure 23) of the "Return Hose Assembly" into the pre-installed male fitting in the port marked "Tank". The fitting will "click" when properly installed.

5B-4 Attach the other end of the "Return Hose Assembly" onto the male end form of the "Return Fuel Filler Tube" installed in step 5B-2. A "click" will be heard when the fitting is properly connected.

5B-5 Any excess fuel hose can be addressed by routing the hose in a fashion to take up the extra length, or a section of the hose can be removed. Push lock splices have been included if you choose to remove the excess hose.

Section 5-C: Fuel Suction Line for AirDog® FP-100!

NOTE: The AirDog® FP-150 requires a High Flow Suction Tube. If you are installing an AirDog® FP-150 skip Section 5-C and go to section 5D!

5C-1. Insert the female quick connect end (see figure 24) of the "Suction Hose Assembly" to the male fitting installed in the "Fuel In" port during step 4-3 of this manual. A "click" will be heard when the fitting is properly connected.

Figure 24

5C-2. Remove the original fuel suction line Quick Connect fitting from fuel tank by squeezing the tabs on the end of the connector together. DO NOT mistake the return line with the suction line. Consult your factory manual if unsure of these procedures.

Fuel Suction Line for AirDog® FP-100, cont'd!

Figure 25

Figure 26

Figure 27



In More Detail

To release the quick-connect fitting from the fuel tank suction tube, push the fitting toward the suction tube. With the plastic tabs firmly depressed, pull the fitting assembly from the suction tube. Hold the Quick Connect Fitting square to the suction tube. It may be difficult to disconnect the fitting it is cocked or becomes cocked during removal.

5C-3. Attach the other end of the "Suction Hose Assembly" to the male quick connect on the top of the fuel module where the factory suction line was once located. A "click will be heard when the assembly is properly connected. (Figure 27)

5C-4. Any excess fuel hose can be addressed by routing the hose in a fashion to take up the extra length, or a section of the hose can be removed. Push lock splices have been included if you choose to remove the excess hose.

INSTALLING THE AIRDOG® FP-150 *HIGH FLOW* SUCTION TUBE

The AirDog® 150 includes a ½" *High Flow* suction tube to accommodate the high flows of this system. To install the ½ suction tube it is necessary to either drop the fuel tank or to lift the truck bed.

NOTE: Should you choose to drop the fuel tank, support the tank as it is when it is installed on the truck. If you let it rest flat on the floor, the tank may squash out and the suction tube will be too short after the tank is re-installed in the truck. The suction tube, being cut too short may suck air as the fuel drops below ¼ tank level.

NOTE: Should you choose to pull the pickup bed to access the tank. Be sure to disconnect the tail light wires, fuel tank filler tube, and any other accessories or components that may be secured to the frame and bed.

When Dropping the Tank, Always Remember Safety First!

Figure 29

Figure 31

Figure 30

If you choose to remove the bed, properly support the truck bed to prevent serious injury or death!

Figure 32

Figure 33

INSTALLING THE HIGH FLOW SUCTION TUBE, Cont'd

NOTE: The fuel tank used for the pictures is an example only and may not be exactly the same as your tank.

IMPORTANT: Select a location for the suction tube that has adequate clearance below the bed. Also consider that under hard acceleration, fuel will migrate toward the back of the fuel tank.

5D-1. Remove the collection basket.

Figure 34

Figure 35

5D-2. Drill a 1-1/8" hole at the selected location in the fuel tank for the suction tube. Hold a container below the drill point to catch debris.

Figure 36

Figure 37

5D-3. Remove all burrs from the edge of the hole.

Figure 38



Figure 39

5D-4. Install the grommet in the new suction tube access hole.

INSTALLING THE HIGH FLOW SUCTION TUBE, Cont'd

5D-5. Measure and cut the suction tube to a length that will allow approximately 1/8" clearance off the bottom of the tank. It is suggested to form the end of the tube similar to Figure 40.

Figure 40

5D-6. Lubricate the bulkhead fitting with motor oil. Pressing firmly, insert the suction tube assembly into the grommet. Be sure the bulkhead fitting is completely seated in the grommet.



Figure 41

Figure 42

5D-7. Re-install the Collection basket.

Figure 43

5D-8. Connect the end of the "Suction Hose Assembly" to the bulk head fitting while it is easily accessible. A "click" will be heard when it is properly installed.

5D-9 Any excess fuel hose can be addressed by routing the hose in a fashion to take up the extra length, or a section of the hose can be removed. Push lock splices have been included if you choose to remove the excess hose

INSTALLING THE HIGH FLOW SUCTION TUBE, Cont'd

5D-10. If the fuel tank was dropped to install the suction tube, re-install the fuel tank. If the truck bed was removed, reinstall the bed.

The *AirDog*® is equipped with a relay controlled wiring harness.

WIRING DIAGRAM (In Red)



The AirDog® wiring harness!

AirDog® Pump Motor Lead

Pressure Sensor/Switch Lead

Indicator Light Lead

Battery Positive Lead

Battery Negative Lead

Mini Fuse Tap Relay Lead

Figure 44

CAUTION: If the ***OPTIONAL*** Low Pressure Indicator Light is not used, be sure to insulate the two (2) #10 Indicator Light connectors to prevent accidental contact.

Securing the Relay and Fuse Holder to the Vehicle

6-1. Secure the relay and fuse holder to the vehicle.

Figure 45

Figure 46

Connecting the AirDog® Relay Control Lead

6-2. Route the ***AirDog®*** 'Relay activation lead', to the fuse panel on the dash to the left of the steering column. Insert the mini fuse tap into a spare fuse holder on the panel that is “hot” when the starter key is turned to the on position.



Figure 47

Figure 48

6-3. ***OR*** if you prefer, route the ***AirDog®*** 'relay activation lead, 'the Red (+) wire with the mini fuse tap attached, to the OE fuel pump. Remove the mini fuse tap and splice the relay lead to the OE fuel pump lead.

NOTE: The power supply leads can be connected to the battery or the alternator. Connecting the power supply leads to the alternator instead of the battery will create a corrosion free connection.

6-4. Route the power supply leads to the alternator. Connect the Black (-) lead to the alternator *Ground* connection.

Connect the Red (+) lead to the alternator *Hot Lead* going to the battery.

Figure 49

Black (-) Red (+)



OR

6-5. Should you choose to connect the power supply leads directly to the battery, connect the RED (+) lead to the POSITIVE (+) post of the driver's side battery. Connect the BLACK (-) lead to the NEGATIVE (-) post on the same battery.

Figure 50



6-6. Route the wiring harness to the ***AirDog®*** and connect the 2 pin Deutsch connector to the corresponding connector on the ***AirDog®***.

Figure 51

INITIAL START PROCEDURE

The ***AirDog®*** is a self priming system, however, to prevent potential damage and reduce the life expectancy of the system, it is recommended to pre-fill only the water separator with diesel fuel before initial startup.

7-1. Pre-fill the water separator with diesel fuel.

7-2. Turn the starter key to the on/run position.

7-3. While the ***AirDog®*** is operating, bleed the fuel line to the engine of air by loosening the fuel line connection at the engine fitting. As soon as the line is purged of air and pure fuel is observed, properly tighten the fuel fitting. **NOTE:** put a rag or shop towel over and around fitting to prevent splatter. Catch all spilled fuel and dispose of properly.

7-4. Start engine!

RECHECK ALL FUEL FITTINGS FOR LEAKAGE AND PROPERLY TORQUE. BE SURE ALL FUEL LINES ARE PROPERLY ROUTED TO PROTECT FROM EXCESSIVE HEAT AND SECURED TO PROTECT FROM CHAFFING AND ABRASION. RECHECK ALL ELECTRICAL LINES, SECURE AS NECESSARY.

Checking Pump Noise!

NOTE: Each AirDog® has been manufactured in a Quality Controlled process and wet tested for operation and performance before shipment. This is a very quiet and smooth running system. With fuel or air alone, the AirDog® fuel pump will run very quietly. However, if any fuel fitting on the vacuum side, between the fuel tank and the AirDog® or the water separator, has been left loose during the installation process, the system may suck air at an excessive rate and will be very noisy. To check for this problem, unscrew the water separator 3 or 4 full turns and activate the AirDog® by turning the ignition switch to on. If the AirDog® runs quietly, then excessive air from a loose fitting or leaking water separator seal is most likely the reason for the excessive noise. Correct as necessary.

A. The seal groove in the 3” filter is a snug fit and on occasion the seal has been found to not be fully seated. Remove the water separator, remove the seal from the top of the nut plate. Clean and lubricate the seal grove. Carefully replace the seal in the grove. Be sure to fully seat the seal.

B. Check all fittings, especially the quick connect at the tank.

Filter Service Recommendations

Plugging of either the fuel filter or the water separator itself will cause low fuel pressure and low flow to the engine. If a low fuel pressure issue exists, replace the fuel filter.

The Water Separator

Replace the water separator every other time you change the Fuel Filter or if it becomes damaged or plugged. It is suggested to check/drain the water separator every three months or as needed should you experience excessive 'water in fuel' conditions. When installing the water separator, be sure to clean the underside of the AirDog® base. Follow the instructions printed on the pre-filter for proper tightening procedures.

CAUTION: Be extremely careful to prevent any contaminates or debris from entering the pre-filter when removing it for cleaning! Large debris will jam the Gerotor and cause the fuse to blow. This is not a warranty item. Should this happen, you can easily put the system back into working order. See the instructions on "How to clean the Gerotor" for proper procedures.

The Fuel Filter

Remove the fuel filter by turning it counter clockwise. Do Not pre-fill the fuel filter with fuel. The AirDog® will fill the filter and prime the system automatically. Follow the instructions on the filter for proper tightening procedures.

CAUTION: Dispose of waste fuel and used filters properly to protect OUR environment!

Cleaning Foreign Debris from the Gerotor Assembly

Step 1
Remove the four (4) socket head cap crews that secure the gerotor cap.

Step 2
Carefully remove the O'ring, you will need to re-use it.

Step 3
Remove and clean the gearotor. Be very careful not to damage the gerotor.

Step 4
Clean the inside of the gerotor pocket.

Step 5
Replace the O'ring and center gear.

Step 6
Align the teeth and install the outer gear.

Step 7
Install the gerotor cap. Be very careful to index the cap to position the wide space between the half moon cuts to the bottom.

Step 8
Replace the cap into position. Be very careful, do not pinch the O'ring. Torque the cap screws. in an opposing pattern.

Installing a New Filter

1. Clean the area around the filter head and groove or seal area.
   NOTE: Lubricate the seal with oil. Do not use diesel fuel to lubricate the seal.

2. Install a new fuel filter on the filter head. Turn clock-wise until the filter contacts the seal. Tighten the filter one full turn or follow tightening instructions on filter after contact with the seal has been made.
   NOTE: It is not necessary to pre-fill the fuel filter!

CAUTION: DO NOT OVER TIGHTEN, OVER TIGHTENING CAN DISTORT THREADS OR DAMAGE THE FILTER SEAL.

3. **To prime the filter,** turn the ignition switch to the on position. Start the engine.

Water Separator

With the engine turned off, pinch off the suction line. Open valve on the bottom of the water separator. Drain into a suitable container until all water has been removed. Close valve. Remove the pinch in the suction.

DRAINING: The water separator should be serviced once a month or when severe water in fuel conditions require.

NOTE: Collect all spilled fuel and dispose of in accordance with federal, state and local regulations.

PUREFLOW AIRDOG

LIFETIME LIMITED EXPRESS WARRANTY

FOR

Covered PureFlow AirDog I, II and Raptor Systems

IMPORTANT NOTICE

TO ACTIVATE YOUR PURFLOW AIRDOG WARRANTY, YOU MUST COMPLETE AND MAIL YOUR WARRANTY CARD TO PUREFLOW AIRDOG WITH A COPY OF YOUR ORIGINAL SALES RECEIPT WITHIN 30 DAYS OF PURCHASE. FAILURE TO COMPLETE AND SUBMIT YOUR WARRANTY CARD WILL RESULT IN A WARRANTY PERIOD OF THE COVERED PRODUCE TO ONE (1) YEAR FROM THE DATE OF PURCHASE.

PureFlow AirDog (hereafter collectively, "SELLER") warrants and guarantees only to the Original Purchaser (hereafter collectively, BUYER) that All PureFlow AirDog Systems (hereafter collectively, PRODUCT) shall be free from defects of materials and workmanship in the manufacturing process for as long as the BUYER owns the PRODUCT.

The Lifetime Limited Express Warranty is limited to the PRODUCT purchased by the original BUYER of the PRODUCT and limited solely to the parts contained within the PRODUCT and EXCLUDES ALL ELSE INCLUDING FILTERS AND WATER SEPARATORS. Any PRODUCT that is in question of Warranty must be returned, shipped prepaid, to PureFlow AirDog. All Warranty claims are subject to the approval of PureFlow AirDog. If it is determined that a Warranty claim exists, PureFlow AirDog will, at its sole discretion, replace the defective PRODUCT with a comparable PRODUCT, repair the defective PRODUCT, or refund the BUYER"S purchase price in exchange for the PRODUCT. Repairs or replacements are warranted for only the remainder of the original warranty period and only to the original BUYER.

Under no circumstances shall the SELLER be liable for any labor charged or travel time incurred in the diagnosis for defects, removal, or reinstallation of the PRODUCT, or any contingent expense.

Under no circumstances will the SELLER be liable for any damage or expense incurred by reason of the use or sale of the PRODUCT.

Other than expressly set forth herein, the SELLER shall in no way be responsible for the proper or improper use and service of the PRODUCT. In no event shall the SELLER be liable for any special, incidental, indirect or consequential damages of any kind or nature, whether or not the BUYER of the PRODUCT was advised of the possibility of damage or harm, arising or resulting from the use or performance of the PRODUCT and BUYER hereby waives the right to any and all such claims.

BUYER, acknowledges that he/she is not relying on SELLER'S skill or judgment to select or furnish goods suitable for any particular purpose and that SELLER has no liability that will extend beyond the scope of the LIMITED EXPRESS WARRANTY contained herein, and BUYER hereby waives all remedies or liabilities, expressed or implied, arising by operation of law or otherwise.(including, without limitation, any obligation of SELLER with respect to fitness for any particular purpose; merchantability; and special, incidental, indirect or consequential damages) or whether or not occasioned by SELLER'S negligence.

SELLER disclaims any warranty and expressly disclaims any liability for personal inquiry or damages related to BUYER'S use of the PRODUCT. BUYER acknowledges and agrees that the disclaimer of any liability for personal injury is a material term for this agreement and BUYER agrees to indemnify SELLER and hold SELLER harmless from any claim related to the PRODUCT and its use or performance. Under no circumstances will SELLER be liable for any damages, liabilities, costs or expenses incurred as a result of or by reason of use, performance or sale of the PRODUCT, including without limitation, any damages, liabilities, costs or expenses incurred by reason of BUYER'S negligence related to those uses of the PRODUCT.

The proper installation of the PRODUCT is the sole responsibility of the BUYER. The SELLER assumes no liability regarding improper installation or misapplication of the PRODUCT.

SELLER hereby provides the following limited warranty as to description, quality, merchantability, fitness for the PRODUCT'S purpose, productiveness, or any other matter of SELLER'S PRODUCT sold herewith. The SELLER shall be in no way responsible for the open use and service of the PRODUCT and the BUYER hereby waives all rights other than those expressly written herein. This Warranty shall not be extended or varied except by a written instrument signed by SELLER and BUYER.

IN THE EVENT THAT THE BUYER DOES NOT AGREE WITH THIS AGREEMENT, THE BUYER MAY PROMPTLY RETURN THE PRODUCT, IN A NEW AND UNUSED CONDITION, WITH A DATED PROOF OF PURCHASE, TO THE PLACE OF PURCHASE WITHIN THIRTY (30) DAYS FROM THE DATE OF PURCHASE FOR A FULL REFUND. THE BUYER AGREES THAT THE INSTALLATION OF THIS PRODUCT CONFIRMS THE BUYER HAS READ AND UNDERSTANDS THIS AGREEMENT AND ACCEPTS THE TERMS AND CONDITIONS OF THIS AGREEMENT.

Warranty Procedure

In the unlikely event a warranty appears as if it may be warranted, the following steps are taken:

1. The customer discussed the symptoms of the problem with a PureFlow AirDog Technician. The customer is to have the system Serial Number and Model Number available for the Technician when the call is made. This will expedite all steps of the process.
2. The customer performs any and all tests requested by the PureFlow AirDog Technician. This is done to isolate the potential problem while eliminating potential installation or maintenance related issues,
3. If the PureFlow AirDog Technician determines based on the customer feedback concerning the requested testing that system may be at fault, the customer is advised that all returned pumps are tested upon arrival and should this returned pump perform at design criteria upon arrival, the customer will be charged a $50.00 fee.
4. The PureFlow AirDog Technician will first request the customer's phone number in the event the phone call is accidentally disconnected and then transfer the customer to a PureFlow AirDog Customer Service Representative. Should a Customer Service Representative not be available, the Technician will offer the Customer the option to hold, call back, or receive a return call.
5. The PureFlow AirDog Customer Service Representative will check to determine if the customer's Warranty Registration Card is on file.
    a. If no Warranty Registration is found, the customer will be required to supply the original purchase receipt showing the purchase date.
    b. If no Warranty Registration is found, the customer will be advised of the options should the system in question is out of the default warranty period (1 year).
6. The PureFlow AirDog Customer Service Representative will request the customer information, including: Name, Address, Phone Number, Model Number, Serial Number, Year / Make / Model of vehicle, Name of Dealer purchased from, Purchase Date, Description of Problem, Customers' understanding of the resolution, and customer credit card information.
7. PureFlow AirDog will cover Ground Shipping charges to ship the replacement unit and will include a prepaid shipping label for the return of the defective unit. Any additional items ordered at the time of the replacement shipment will include their portion of the shipping cost.
8. A period of 15 Calendar Days from the time of shipment is provided for the receipt of the defective unit at the PureFlow AirDog facility. Failure to return ship the defective unit to arrive within the defined time period will result in a charge of $250.00 against the customer's credit card as the purchase cost of the defective unit.